



## Performance Header Transport.

Loading and transporting your MacDon headers just got a whole lot easier with MacDon TR Series Trailers. Specifically built for your MacDon header, the swan neck chassis design provides on-road precision for up to 40km/h (24mph) road speeds.\*

*Here's everything MacDon TR Series Trailers can do for your operation:*

- A Precision Transport.**  
The swan neck chassis design provides on-road precision, allowing the trailer to follow the towing vehicle's tracks closely. This design lets you handle tight roadways and crossings with confidence.
- B Road Ready Homologation.**  
MacDon Trailers can be used with M1 Series Windrowers, Combines, Tractors, or Trucks. MacDon TR Series Trailers have EU homologation for 40km/h (24mph) and comply with European road standards.\*
- C Easy On. Easy Off.**  
Loading and unloading your MacDon headers just got a whole lot easier with MacDon-specific header supports/hookups.
- D Hit the Brakes.**  
The inertia-activated brake activates the front and rear drum brakes via cable tension. Inertial braking allows for smooth handling of the trailer by the towing vehicle.  
Trailers are equipped with a hand-activated park brake, wheel chocks, and on-frame wheel chock storage.
- 1 Spare Tire Option**  
Conveniently stored on-frame to quickly get you back on the road and in the field harvesting.
- 2 On-Frame Storage Options**  
An optional storage box is cleverly attached on-frame and allows storage of tools and performance options like crop dividers and crop lifters. A vertical knife storage rack is also available.

*\*Always follow local traffic laws and regulations.*

*Only use towing vehicles rated to tow MacDon Trailers.*



**TR SERIES TRAILERS - SPECIFICATIONS**

|                      |  |
|----------------------|--|
| <b>Model</b>         | TR25   |
| <b>Weight</b>        | 1710 kg (3770 lbs)   |
| <b>Dimensions</b>    | Length: 12 m (39'4"); Width: 2.16 m (7'1")   |
| <b>Wheels/Brakes</b> | P264-75 R15 radial tires; fender kit (option); inertial braking system; drum brakes; with reversing mechanism  |
| <b>Parking</b>       | Manual park brake; wheel chocks and wheel chock storage  |
| <b>Header Hookup</b> | MacDon specific supports; adjustable alignment gauge; adjustable support arm with turnbuckles; support arms adjustable laterally; rear tie-down locations; lift-assisted tow bar |
| <b>Legal</b>         | Homologated for European Union; 40 km/h (24 mph) road speed*   |
| <b>Storage</b>       | On-board storage box (option); On-board vertical knife storage rack (option)   |

\*Always follow local traffic laws and regulations. Only use towing vehicles rated to tow MacDon Trailers.

\*\*All listed weights are approximations and will vary depending on options installed.

**TR SERIES TRAILER/HEADER COMPATIBILITY CHART**

| Header Size  | TR25 Compatible Header Models                           |
|--------------|---|
| 4.6 m (15')* | D50, D60, D65, D1, D1X, PW8                             |
| 6.1 m (20')* | D50, D60, D65, D1, D1X                                  |
| 7.6 m (25')* | D50, D60, D65, D1, D1X, FD125                           |
| C Series     | Max header size = 12 row x 50.8 cm (20 in.) row spacing |

\*D1 Headers equipped with a TM100 Tractor Mount can be used with MacDon Trailers.

